Previous Doc Next Doc Go to Doc# First Hit

> Generate Collection **Print**

L4: Entry 142 of 206

File: JPAB

May 28, 1982

PUB-NO: JP357085953A

DOCUMENT-IDENTIFIER: JP 57085953 A

TITLE: CARBIDE DISPERSION TYPE SINTERED IRON ALLOY WITH SUPERIOR WEAR RESISTANCE

PUBN-DATE: May 28, 1982

INVENTOR-INFORMATION:

NAME

COUNTRY

IIJIMA, MASAYUKI AKUTSU, HIDETOSHI ANZAI, KATSUAKI

US-CL-CURRENT: 75/246

INT-CL (IPC): C22C 38/26; C22C 38/38; C22C 33/02

## ABSTRACT:

PURPOSE: To enhance the wear and scuffing resistances of the resulting titled alloy by providing a composition consisting of C, Cr, Mn, one or more among P, B and Si, one or more among Zr, Hf, Nb and Ta, and the balance Fe.

CONSTITUTION: This carbide dispersion type sintered Fe alloy has a composition consisting of, by wt.,  $0.5 \sim 3\%$  C,  $5 \sim 20\%$  Cr,  $0.05 \sim 5.0\%$  one or more among P, B and Si,  $0.05\sim3.0$ % Mn,  $0.05\sim10.0$ % one or more among Zr, Hf, Nb and Ta, and the balance Fe with inevitable impurities or further contg.  $0.5\sim10.0\%$  Mo and/or W and/or  $0.5 \sim 10.0$ % one or more among Ni, Co and Cu. This sintered alloy has superior wear, scuffing and pitting resistances and does not damage the opposite member.

COPYRIGHT: (C) 1982, JPO& Japio

Previous Doc Next Doc Go to Doc#